



1KG - 5KG

# ALKALINE CLEANER FOR PORCELAIN STONEWARE SURFACES

- Specifically formulated cleaner for the removal of epoxy grouts.
- · Non-foaming.
- · Suitable for both mechanical and manual use.

## **EPOXY FREE**

Specialized cleaner for removing epoxy grout residues from porcelain stoneware surfaces with porosity or texture that tends to retain grout. Through a softening process, it completely eliminates epoxy resins without altering the joints or damaging the tiles.

#### How to use

- Perform a preliminary test on a tile to verify results and contact time.
- Apply the product to the surface using a white, green, or brown pad, depending on the type of material.
- Let it act for 20–30 minutes, scrubbing with the pad every 5 minutes.
- After 20–30 minutes, wipe the surface with a sponge and water (preferably warm).
- Remove residues with a cloth or wet vacuum. Rinse with water.
- · Repeat the process if necessary.
- Do not use on rubber flooring.



## **Dilution**

Use undiluted.

## **Technical data**

- · Appearance: Liquid.
- Contains: Sodium metasilicate pentahydrate.

## SURFACES TECHNOLOGICAL ABRASIVES SPA

## **Legal Headquarters**

Via A. De Gasperi, 6/8 24069 Cenate Sotto (BG) Tel. +39 035 943636

## **Commercial Headquarters**

via G.F. Ferrari Moreni 2/8 41049 Sassuolo (MO) Tel. +39 059 8350999

