

# EPOXY FREE

**POWER  
CLEAN** Install Pro

**1KG - 5KG**

## ALKALINE CLEANER FOR PORCELAIN STONEWARE SURFACES

- Specifically formulated cleaner for the removal of epoxy grouts.
- Non-foaming.
- Suitable for both mechanical and manual use.

### EPOXY FREE

Specialized cleaner for removing epoxy grout residues from porcelain stoneware surfaces with porosity or texture that tends to retain grout. Through a softening process, it completely eliminates epoxy resins without altering the joints or damaging the tiles.

### How to use

- Perform a preliminary test on a tile to verify results and contact time.
- Apply the product to the surface using a white, green, or brown pad, depending on the type of material.
- Let it act for 20–30 minutes, scrubbing with the pad every 5 minutes.
- After 20–30 minutes, wipe the surface with a sponge and water (preferably warm).
- Remove residues with a cloth or wet vacuum. Rinse with water.
- Repeat the process if necessary.
- Do not use on rubber flooring.

### Dilution

Use undiluted.

### Technical data

- Appearance: Liquid.
- Contains: Sodium metasilicate pentahydrate.



### SURFACES TECHNOLOGICAL ABRASIVES SPA

#### Legal Headquarters

Via A. De Gasperi, 6/8  
24069 Cenate Sotto (BG)  
Tel. +39 035 943636

#### Commercial Headquarters

via G.F. Ferrari Moreni 2/8  
41049 Sassuolo (MO)  
Tel. +39 059 8350999

[www.surfaces-group.it/en/](http://www.surfaces-group.it/en/)



**SURFACES GROUP**